

Note:
1 materials:
1-1 needle: C3604
1-2 tube: C3604
1-3 spring:SUS304
2 surface treatment:
2-1 needle:
Gold plated 5 uin / Ni based 50-100uin
2-2 casing:
Gold plated 5 uin / Ni based 50-100uin
3 Mechanical properties:
3-1 stretch:
The working height of 5.4 mm
elastic 70g ±20%
3-2 durability: 10000 times
4 electrical properties:
4-1 rated voltage: 12V
4-2 rated current: 2.0A
4-3 contact resistance:50mohm
5 ecological environment parameters:
5-1 high temperature resistance of 260 DEG C
5-2 storage temperature range:
Between -40 to 70 DEG C.
5-3 humidity range:
10%RH to 90% relative humidity.

Sumpak 深圳市森柏科技有限公司	GENERAL TOLERANCE: XX. ±0.40; X. ±0.25; .X ±0.10; .XX ±0.05; .X° ±1.0°; .XX° ±0.5°	SCALE: 15:1	制图 王文英	DATE 20-04-28	DRAWING NO: SB-BJ2065	Product Name: 2.0-6.5MM弹簧针	REV. A
		UNIT: mm	批准	DATE	Material number:		SHEET 1/1
		SIZE: A4	审核	DATE			